


Flow valve Throttle valve

$Q_{\max} = 12 \text{ gpm}$, $p_{\max} = 3600 \text{ psi}$


Direct acting, spool type, proportional solenoid

Type series: MDRPA-DGE-10-...



- Screw-in cartridge valve for cavity DD
- All external parts with zinc-nickel plating according to DIN EN ISO 19598
- Installation in threaded port body type DDY-12
- High pressure wet-armature solenoids
- Various plug-connector systems and voltages are available

Symbol



Description

The direct acting proportional throttle valve is a high-performance threaded screw-in cartridge valve in size 10. The valve is designed on the sliding-spool principle. When de-energized, the connection from A to B is disabled, and the additional port Z is used for secondary unloading from B to Z (in applications where a load-sensing line is required). In both mobile and industrial

applications, these valves are the ideal choice for responsive and controlled lifting and lowering movements where large pressure differentials exist. The types "300" and "400" with nominal flow rates of 30 and 40 l/min must only be used in combination with an inline compensator or a bypass hydrostat (see "Technical Data").

Technical data

General characteristics	Description, value, unit
Function group	flow valve
Function	throttle valve
Design	screw-in cartridge valve
Controls	proportional solenoid
Characteristic	direct acting, spool type
Construction size	NG 10
Thread size	M24×1,5
Mounting attitude	unrestricted (preferably vertical, coil down)
Weight	2.54 lb
Cavity acc. factory standard	DD
Tightening torque steel	48 ft·lb
Tightening torque aluminium	37 ft·lb
Tightening torque tolerance	± 10 %
Minimum ambient temperature	- 22 °F
Maximum ambient temperature	+ 122 °F
Surface protection	all external parts with zinc-nickel plating according to DIN EN ISO 19598
Sealing material	see ordering code
Seal kit order number	NBR: DS-265-N / FKM: DS-265-V

Hydraulic characteristics	Description, value, unit
Maximum operating pressure	3600 psi
Maximum flow rate	12 gpm
Nominal flow rate	Used with pressure-compensator cartridges: 11 gpm: max. Δp 130 psi 8 gpm: max. Δp 200 psi Used without pressure-compensator cartridges: 5.25 gpm 3.25 gpm
Flow direction	see symbol
Hydraulic fluid	HL and HLP mineral oil according to DIN 51 524; other fluids on request!
Minimum fluid temperature	- 22 °F
Maximum fluid temperature	+ 158 °F
Viscosity range	15 ... 380 mm²/s (cSt)
Recommended viscosity range	20 ... 130 mm²/s (cSt)
Minimum fluid cleanliness (cleanliness class according to ISO 4406:1999)	class 18/16/13


Electric characteristics

Actuator type	solenoid coil
Solenoid coils type	□36
Supply voltage DC	12 V DC 24 V DC
Control current	12 V = 0...1400 mA 24 V = 0...700 mA
Relative duty cycle	100 %
Coil resistance R	cold value at 20°C: 12 V = 6.4Ω / 24V = 24.5Ω cold value at -25°C: 12 V = 5.2Ω / 24V = 20.0Ω max. warm value: 12 V = 10.0Ω / 24V = 38.4Ω
Inductance	Non-operated measured, at 0,1 mArms / 1 kHz 12 V = 13 mH / 24 V = 54 mH
Recommended PWM frequency	150...200 Hz
Response sensitivity with PWM	< 1 % I_{max}
Reproducibility with PWM	< 2 % Q_{nenn}
Hysteresis with PWM	2...4 % I_{max}
Reversal error with PWM	2...4 % I_{max}
Electrical connection coil	DIN EN 175301-803, 3-pole 2 P+E (IP 65)
Protection class solenoid coil to ISO 20 653 / EN 60 529	IP65, see Ordering code


Performance graphs

measured with oil viscosity 33.0 mm²/s (cSt)


$\Delta p = f(Q)$ Pressure drop-flow rate characteristic




$\Delta p = f(Q)$ Pressure drop-flow rate characteristic




$\Delta p = f(Q)$ Pressure drop-flow rate characteristic




$\Delta p = f(Q)$ Pressure drop-flow rate characteristic




$Q = f(\Delta p:I)$ Flow rate adjustment




$Q = f(\Delta p:I)$ Flow rate adjustment




$Q = f(\Delta p:I)$ Flow rate adjustment




$Q = f(\Delta p:I)$ Flow rate adjustment




$Q = f(I:\Delta p)$ Flow rate adjustment




$Q = f(I:\Delta p)$ Flow rate adjustment



$Q = f(I:\Delta p)$ Flow rate adjustment




$Q = f(I:\Delta p)$ Flow rate adjustment



Installation

Beispiel für die Masseinheit:
Example for the dimensional units:

0.79 = 0.79 mm millimeter
(.031) = 0.031" inch



NOTE!

- Observe tightening torques M_A .
- Mount the valve preferably suspended (automatic air bleed).
- The valve is factory-set, no further adjustments are necessary.



ATTENTION!

Only qualified personnel with mechanical skills may carry out the following work:

- installation and, if necessary, adjustment.
- inspection and, if necessary, replacement of the seals shown in the illustration. New seals must only be installed after being oiled or greased (seal kit; see "Technical Data").

Solenoid orientation


1. Slightly loosen the mounting bolts ①.
2. Align the solenoid ② so that the plug connector ③ is facing the required direction.
- 3.



INFO

Before tightening the mounting bolts ①, make sure there is an even gap ⑤ all around between the flange ④ and the solenoid ②.

Tighten the mounting bolts ① on the flange ④ (observe tightening torque M_A).




Application examples

Used with secondary unloading


Application example with secondary unloading. Includes the following functions:

- Valve de-energized = unpressurized flow through bypass compensator (BDW).
- Valve energized = stepless and load-independent speed control at V1.
- Valve energized = LS operation with fixed-displacement pump.



Classic Combination

Application example of types "300" and "400" with nominal flow rate of 30 and 40 l/min (8 and 11 gpm) for parallel operation of two actuators (V1 and V2) with different load pressures. To avoid exceeding the maximum permissible Δp from A to B, inline pressure-compensator cartridges (IDW) are positioned before the throttles. The connection from B to Z unloads the LS line when the actuator is not in use. When both actuators are unloaded, unpressurized flow circulates through the bypass pressure-compensator cartridge (BDW).



Ordering code

Ex.

MD	R	P	A
----	---	---	---

 -

D	G	E
---	---	---

 -

10

 -

120	—
-----	---

 -

5

24	D	—
----	---	---

MD	=	throttle valve, direct acting
R	=	proportional-solenoid operated
P	=	cartridge design
A ... Q	=	standard model according to valid data sheet
Z ... R	=	special model (on request)
D	=	cavity type DD
G	=	de-energized closed
E	=	port Z for secondary unloading
10	=	nominal size 10
120	=	nominal flow rate = 12 l/min
200	=	nominal flow rate = 20 l/min
300	=	nominal flow rate = 30 l/min: max. Δp 14 bar
400	=	nominal flow rate = 40 l/min: max. Δp 9 bar
(blank)	=	NBR (nitril-butadien-rubber / BUNA) seals (standard)
V	=	FKM (fluorocarbon rubber / VITON) seals (special seals on request)
1 ... 9	=	technical design no. (omit when ordering)
...	=	voltage e.g. 24 (24 V)
D	=	current DC
(blank)	=	ISO 4400 / DIN 43 650 mating plug (standard, IP 65)
M100	=	DIN EN 175301-803 connection, 3-pole 2 P+E (IP 65)
J	=	Junior Timer plug connection, 2-pole radial (IP 65)

} connection without mating plug



HINWEIS!

Die Typen "300" und "400" mit Nennvolumenstrom 30 und 40 l/min dürfen nur in Kombination mit einer Inline- oder Bypass-Druckwaagepatrone eingesetzt werden (siehe "Technische Daten").

Related data sheets

Reference	Description
400-P-040011	form tools
400-P-060121	cavity DD
400-P-740112	threaded port body DDY-12

info.ch@bucherhydraulics.com

www.bucherhydraulics.com

© 2026 by Bucher Hydraulics AG Frutigen, 3714 Frutigen, Switzerland

All rights reserved.

Data is provided for the purpose of product description only, and must not be construed as warranted characteristics in the legal sense. The information does not relieve users from the duty of conducting their own evaluations and tests. Because the products are subject to continual improvement, we reserve the right to amend the product specifications contained in this catalogue.